



Effective: November 29, 2024

Submittal Data Information

0034ePlus™

ECM High-Efficiency Circulator

101-193

Supersedes: September 20, 2023

Job: _____ Engineer: _____ Contractor: _____ Rep: _____

ITEM NO.	MODEL NO.	

Specifications

- Maximum Shut-off Head: 34 feet
- Maximum Flow: 50 gpm
- Maximum Operating Pressure: 150 psi (10.3 bar)
- Maximum Water Temp: 230°F (110°C)
- Minimum Water Temp: 14°F (-10°C)
- Electrical specifications:
 - Voltage: 115V/208/230, 50/60 Hz Single phase
 - Operating Power Range: 10 - 170W
 - Max. AMP Rating: 1.48 (115V) - 0.70 (230V)
- Equipped with a Cast Iron or Stainless Steel casing
- Suitable for chilled water systems
- Stainless Steel model suitable for open loop potable water systems
- Taco circulators are for indoor use only
- Acceptable for use with water or maximum of 50% water/glycol solution
- 6.5" Flange to Flange dimension retrofits most circulators in its class

Materials of Construction:

Casing: Cast Iron or Stainless Steel

Stator Housing: Composite

Control Base: Composite

Control Cover: Composite

Cartridge: Composite

Impeller: Composite

Shaft: Ceramic

Rotor: Neodymium

Bearings: Ceramic

Thrust Bearing: Carbon



O-Ring & Gaskets: EPDM

Applications


Cast Iron Model: Closed loop, pressurized heating and chilled water HVAC systems

Stainless Steel Model: Open loop, potable water systems

The 0034ePlus is a high-performance, variable speed, wet-rotor circulator with high-efficiency ECM permanent magnet technology. With 5 easy settings and an intuitive digital interface, its variable speed performance curves are equivalent to the Taco 009, 0010, 0011, 0012, 0012 3-Speed, 0013, 0013 3-Speed & 0014. Ideal for large residential and light commercial hydronic heating, chilled water cooling and domestic hot water systems. The 0034ePlus reduces power consumption by up to 85% compared to equivalent AC permanent split capacitor circulators.



Flange Orientation




Pump Dimensions & Weights

Model Number	Casing	Flange Type	A	B	C	D	F	G	Lbs. [kg]
Inches [mm]									
0034eP-F2	Cast Iron	R	8.05" [205]	6.22" [158]	3.25" [83]	3.20" [81]	6.22" [158]	7.05" [179]	10.5 [4.8]
0034eP-SF2	Stainless Steel								

Electrical Data


Model	Volts	Hz	Ph	Max Amps	Watts	RPM
All Models	115/208/230	50/60	1	1.48	10 - 170	830 - 4300
Motor Type	ECM, Permanent Magnet, Electronically Protected					

Rotatable Control Cover to allow mounting in any orientation



Model #: 0034eP
CIRCULATOR PUMP CEI: 0.41 (ER 154)

ENERGY RATING



Note: The ER value is dependent on the selected control. Multiple options may be available on this pump, as follows:

- Full Speed
- Pressure (Rated)
- External Input Signal and Other Controls

Power savings (watts) over a baseline case can be estimated by multiplying the ER by WAP and multiplying by 7.46. Multiplying power savings by operating hours and cost of energy will yield estimated cost savings.

47PMVB

er.pumps.org

Apr 2021





Intertek
4001998
CONFORMS TO:
UL STD. 778
CERTIFIED TO:
CAN/CSA STD.
C22.2 NO. 108

Certified to
NSF/ANSI CAN 61
& 372
Stainless
Steel Model



TacoAdapt™ Mode:

TacoAdapt™ is an operating mode designed for constant circulation systems. On this setting, the circulator will sense changes in system flow and head conditions and adjust the operating curve automatically.





Constant Pressure Mode:

Circulator will vary speed to maintain desired feet of head constant pressure curve. There are 5 setting options: 6 - 30 feet.





Variable Fixed Speed Mode:

Circulator operates at fixed speed between 1 - 100%




Proportional Pressure Mode:

Circulator will vary speed to maintain desired feet of head proportional pressure curve. There are 5 setting options: 8.2 - 28.6 ft.




0-10V DC or PWM External Input:

The circulator will vary its speed and performance based on a 0-10V DC analog or PWM digital signal external input.




0-10V

PWM (Pulse Width Modulation)



Power Consumption 0034ePlus High-Efficiency Circulator 0-10V DC Curves



0-10V

