

Effective: August 15, 2005

Supersedes: July 1, 2005

Job: _____ Engineer: _____ Contractor: _____ Rep: _____

ITEM NO.	MODEL NO.	

Materials of Construction

Bracket: Die Cast Aluminum
 Shaft: Carbon Steel
 Shaft Sleeve: Copper
 Impeller: Noryl®
 Face Plate: 305 Stainless Steel
 Coupler: Cast Zinc Spring Coupler or Woods 3-J: Aluminum Hub, EPDM Insert
 Mechanical Seal: Carbon/Ceramic
 Cup & Bellows: Buna
 Spring, Holder, Retainer: Stainless Steel

Electrical Data


Model	Volts	Hz	Ph	RPM	HP	Amps
RPK-A-100	115	60	1	1725	1/12	2.0
RPK-B-101	115	60	1	1725	1/6	4.4
RPK-C-100	115	60	1	1725	1/6	4.4
RPK-C-101	115	60	1	1725	1/4	4.4
RPK-C-102	115	60	1	1725	1/3	5.0
RPK-D-100	115/230	60	1	1725	1/2	6.0/3.0
RPK-D-101	115/230	60	1	1725	3/4	9.0/4.5
RPK-D-102	115	60	1	1725	1/4	4.4
RPK-D-103	115	60	1	1725	1/3	5.0
RPK-D-104	115/230	60	1	1725	1/2	6.0/3.0
RPK-D-200	208-230/460	60	3	1725	1/2	2.1-2/1
RPK-D-201	208-230/460	60	3	1725	3/4	2.6/1.3
RPK-D-204	208-230/460	60	3	1725	1/2	2.1-2/1

Open Drip Proof
 Resilient Mount - 1/12HP through 1/2HP
 Class B Insulation


Automatic Thermal Overload
 C-Face Mount - 3/4HP
 Capacitor Start

Performance Data

Max Temp: 225°F
 Max WP: 125 psi



RPK A—C MODEL BEARING ASSEMBLIES



RPK D MODEL BEARING ASSEMBLIES

Pump Dimensions & Weights

	A		B		C		D		E		Ship Wt.	
Model	in.	mm	in.	mm	in.	mm	in.	mm	in.	mm	lbs.	Kg
RPK-A-100	8-5/16	211	2-3/4	70	14-3/8	365	3-15/16	84	1-1/2	38	21	9.5
RPK-B-101	8-5/16	211	3-5/16	84	14-1/2	368	3-9/16	90	1-1/2	38	23	10.4
RPK-C-100	8-5/16	211	4-1/4	108	13	330	3-9/16	90	1-1/2	38	24	10.9
RPK-C-101	8-5/16	211	3-7/8	98	15-1/8	384	3-9/16	90	2	51	24	10.9
RPK-C-102	8-5/16	211	4-1/4	108	15-1/8	384	3-9/16	90	2	51	25	11.3
RPK-D-100	9-1/16	230	4-3/4	120	16-9/16	421	4-5/8	117	2	51	31	14.0
RPK-D-101	9-13/16	249	5-1/4	133	17-5/16	440	4-5/8	117	2	51	35	15.9
RPK-D-102	8-1/4	210	5	127	15-3/4	400	4-5/8	117	1-1/2	38	25	11.3
RPK-D-103	8-1/4	210	5-1/4	133	15-3/4	400	4-5/8	117	1-1/2	38	26	11.8
RPK-D-104	9-1/16	230	5-1/4	133	16-3/4	425	4-5/8	117	1-1/2	38	31	14.0
RPK-D-200	8	203	4-3/4	120	15-7/16	392	4-5/8	117	2	51	29	13.2
RPK-D-201	8-7/8	225	5-1/4	133	16-5/16	414	4-5/8	117	2	51	29	13.2
RPK-D-204	8	203	5-1/4	133	15-11/16	398	4-5/8	117	1-1/2	38	28	12.7

