

FI Series Pump | Submittal Data

Submittal No: 301-1488D | Model: 8013D | RPM: 1160 - 60 Hz | Effective: January 27, 2020 | Supersedes: December 1, 2018

JOB: _____

REPRESENTATIVE: _____

ENGINEER: _____

CONTRACTOR: _____

PRODUCT DATA

ITEM NO. _____ MODEL NO. 8013D

IMPELLER DIAMETER _____ HORSEPOWER _____

GPM _____ VOLTAGE _____

HEAD/FT _____ RPM 1160

WEIGHT _____ PUMP/MOTOR _____

DIMENSIONS

Model No. | 8013D
Flange Size (Suction x Discharge) | 10 x 8 (254 x 203)

HORSEPOWER		15	20	25	30	40	50
ODP	MOTOR FRAME	284T	286T	324T	326T	364T	365T
	G MAX	25.07 (636)		23.69 (601)		29.83 (757)	
	MAXIMUM ASSEMBLY WEIGHT LBS. (KG)	1443 (654)		1533 (695)		2007 (911)	
TEFC	MOTOR FRAME	284T	286T	324T	326T	364T	365T
	G MAX	27.89 (708)		30.52 (775)		33.61 (853)	
	MAXIMUM ASSEMBLY WEIGHT LBS. (KG)	1443 (654)		1533 (695)		2007 (911)	
A		ANSI Class 125: 10 (254)					
		ANSI Class 250: 10.69 (271)					
B		ANSI Class 125: 19 (483)					
		ANSI Class 250: 19.5 (495)					
C		25.17 (639)					
D		60.0 (1525)				74.0 (1880)	
E		ANSI Class 125: 2.38 (60)					
		ANSI Class 250: 1.69 (43)					
F		16.59 (421)					
J		ANSI Class 125: 31.63 (803)					
		ANSI Class 250: 32.32 (821)					
K		23.67 (601)					
N		2 (51)					
P		56.0 (1422)				70.0 (1778)	

Configuration	DOE Basic Model Number	PEI Value		Energy Rating
Bare Pump	N/A	PEI _d	N/A	N/A
Pump + Motor	N/A	PEI _d	N/A	N/A

N/A=NOT WITHIN DOE SCOPE



OPERATING SPECIFICATIONS

FLANGE	PRESSURE	TEMPERATURE
ANSI Class 125	175 PSIG* (1210 KPA)	250°F (120°C)
ANSI Class 250	300 PSIG** (2070 KPA)	250°F (120°C)

Motors: All NEMA Standard (T Frame)

* In accordance with ANSI Standard B16.1 Class 125

** In accordance with ANSI Standard B16.1 Class 250



English dimensions are in inches. Metric dimensions are in millimeters.
Metric data is presented in (). Do not use for construction purposes unless certified.

MATERIALS OF CONSTRUCTION		CASING	COVER	IMPELLER	WEAR RING	SHAFT	SHAFT SLEEVE	MECHANICAL SEAL	SEAL FLUSH LINE ASSEMBLY
STANDARD CONSTRUCTION	125# FLANGE	Cast Iron ASTM A48/A48M-03 Class 30A	Cast Iron ASTM A48/A48M-03 Class 30A	Bronze ASTM B584 ALLOY C83600 or C84400	N/A	Stainless Steel TYPE 416™T ASTM A582	Bronze ASTM B584-98A C92200	Ceramic/EPT	N/A
	250# FLANGE	Ductile Iron ASTM A536-84 Grade 65-45-12	Cast Iron ASTM A48/A48M-03 Class 30A	Bronze ASTM B584 ALLOY C83600 or C84400	N/A	Stainless Steel TYPE 416™T ASTM A582	Bronze ASTM B584-98A C92200	Ceramic/EPT	N/A
OPTIONAL	125# OR 250#	N/A	N/A	Stainless Steel ASTM A351/A 351M-08	Bronze ASTM B584-98A C92200	N/A	Stainless Steel TYPE 303 ASTM A276	Tyngsten Carbide /EPT or Silicon-Carbide/EPT	Copper & Brass C3600


N/A - Not Available



FI Series | Model: 8013D | 1160 RPM

Curve No. 4089 | Min. Imp. Dia. 9.5" | Size 10x8x13.5 | January 22, 2020

Energy Efficiency Rating: DOE Basic Model Number: N/A @1160RPM
Pump & Motor: PEI_{CL}: N/A @1160RPM



COMMENTS