

4900 Series Removable Cover, Hi-Velocity Air Separators Submittal Data

Submittal No: 401-218 | Effective: June 22, 2022 | Supersedes: November 30, 2017

JOB:		REPRESENTATIVE:					
ENGINEER:		CONTRACTOR:					
PRODUCT DATA		←					
ITEM NO	LOCATION	T					

SPECIFICATIONS

MODEL NO. _

GALLONS _

- Designed and constructed per ASME Code Section VIII Div. 1
- Registered with the National Board of Pressure Vessel Manufacturers
- Standard Design Pressure and Temperature: 150 psi @ 240°F
 Construction: Carbon Steel with exterior red oxide primer finish
- 304 Stainless Steel Coalescence Pall Rings
- Taco 4900 units are designed to be self-supporting in the piping system. Factory review is necessary should any piping loads be present.

_ QUANTITY

CAUTION: LIFTING LUGS FOR RIGGING AND LIFTING USE ONLY, NOT FOR ANCHORING OR HANGING.

FACTORY INSTALLED

- · Air Vent is suitable for water, max. 50% glycol
- Blowdown Valve
- Flush Valve

OPTIONS

- High Power Switchable On/Off Style Magnet-Consult factory
- Higher Design Pressures and Temperatures
 - 250 psi @ 240°F, Available
 - 300 psi @ 240°F, Available

A A AIR VENT LIFTING LUG (2) 180° APART 4" (TO REMOVE BASKET) H BE PROVABLE COVER ASSEMBLY BASKET BASKET



SIZES & DIMENSIONS

All dimensions shown are subject to change and should not be used for prepiping. Contact your local Taco representative should certified dimensional drawings be required.

PIPE SIZE	MODEL NUMBER	A DIA. (INCH)	B MAX. (INCH)	C (INCH)	D (INCH)	E (INCH)	F DIA. (INCH)	G (INCH)	H (INCH)	K (INCH)	GPM @ 11ft/sec	APPROX. WEIGHT (LBS.)
18	4918ADHR-150	42	134 5/16	54	67 3/4	10 1/2	35	7 5/8	19	48	8246	4250
20	4920ADHR-150	48	145 3/16	62	80 3/4	12	40	7 9/16	22	48	10238	5565
22	4922ADHR-150	54	157	68	87 1/4	13 1/2	44	8	24	60	11874	7490
24	4924ADHR-150	54	162	68	88 3/4	13 1/2	44	8	24	60	14245	7640
26	4926ADHR-150	60	179 3/4	76	98 1/4	15	54	8 3/4	24 3/8	48	17167	11505
30	4930ADHR-150	66	201	82	110	15	58	8 1/2	25	48	23037	11260
36	4936ADHR-150	84	234 3/16	104	129 1/4	15	72	9 7/16	33 5/8	48	33457	22900

COMMENTS

