

# **Submittal Data Information**

101-036

# 00® Timers/Aquastat

**Effective**: 12/06/24 **Supersedes**: 09/04/19

Job: Eng	neer:	Contractor:	Rep:
ITEM NO.	MODEL NO.		

# 24 Hour Analog Clock Timer Performance Data — #265-1

Electrical Characteristics: 115/60/1

Timer Switch: 16A @115V Timer Interval: 15 Minutes

Clock face: Hour and Minute Hands Manual Switch: I Permanently ON

① Automatic Operation

O Permanently OFF

## 7 Day Digital Timer Performance Data — #265-DT

Input Voltage: 120 VAC, 60 Hz Resistive (Heater): 15 A, 120 VAC

Tungsten (Incandescent): 1000 W, 120 VAC Inductive (Fluorescent): 12 A, 120 VAC

Motor: 1/2 HP, 120 VAC

# Temperature Aquastat — Snap Action Temperature Switch — #563-2

Electrical Characteristics: 115/60/1 Connections: 1/2" (Snap on circ. body)

3/4" Copper pipe

Temperature Setting: ON @ 95°F

OFF @ 115°F

Contacts: 7 amp SPDT Switch Wire Leads: 18" – Type 18-2,

Round Premium Cable

# **Application**

The Taco Clock Timers and Temperature Aquastat are designed to control the operation of Taco circulators on Domestic Hot Water Recirculation Systems for maximum comfort and energy efficiency. They are adaptable to any 00° Series circulator by attaching the enclosure or wiring to the electrical box.

## 24 Hour Analog Timer

Operates the circulator at the same pre-set times every day. Time intervals are in 15 minute increments. This user friendly clock has a raised minute hand for easy adjustments, quick-set trippers and an operation switch for Manual ON/OFF or Automatic modes.

## 7-Day Digital Plug-in Timer

Twenty-eight programmable events allow you to customize the hot water run times to meet the household demand. Its intuitive logic can automatically adjust to daylight savings time, and the convenient dial simplifies programming. A battery backup will retain your settings for up to three months with no power.

## **Temperature Aquastat**


Controls pump operation to maintain system temperature between 95°F and 115°F. Easy clip-on Aquastat attaches directly to 3/4" pipe or a 1/2" sweat pump casing.

# **Shipping Weight**


Model	ltem	Lbs.	Kg
265-1	Analog Timer	.75	.35
265-DT	Digital Timer	.5	.23
563-2	Aquastat	.25	.11



FOR INDOOR USE ONLY







**Assembled Timer/Aquastat** 

