

KS Series Pump | Submittal Data

Vertical Split Coupled Pumps

Submittal No: 301-1717 | Model: 1016 | RPM: 1760 - 60 Hz | Effective: December 22, 2022 | Supersedes: February 28, 2019

JOB: _____

REPRESENTATIVE: _____

ENGINEER: _____

CONTRACTOR: _____

PRODUCT DATA

ITEM NO. _____ MODEL NO. 1016

IMPELLER DIAMETER _____ HORSEPOWER _____

GPM _____ VOLTAGE _____

HEAD/FT _____ RPM 1760

WEIGHT _____ PUMP/MOTOR _____

SUPPORT STAND OPTION YES NO
(Ductile Iron ASTM A536-84 Grade 65-45-12)

DIMENSIONS

Model No. | 1016
Flange Size (Suction x Discharge) | 10 x 10 (254 x 254)

HORSEPOWER		100	125	150	200		250	300	
MOTOR FRAME	TEFC	405CZ		444TC	445TC		447TC	449TC	449TC
	ODP	404CZ	405CZ		444TC	445TC		447TC	449TC
WEIGHT WITHOUT OPTIONAL STAND LBS (KG)		2969 (1347)		3562 (1616)			4474 (2029)		
WEIGHT WITH OPTIONAL STAND LBS (KG)		3069 (1392)		3662 (1661)			4574 (2074)		
FLANGE SIZE ASA		10 (254)							
A*		ANSI CLASS 125: 26.08 (662)							
		ANSI CLASS 250: 26.77 (680)							
B*		ANSI CLASS 125: 23.08 (586)							
		ANSI CLASS 250: 23.76 (604)							
C		13.65 (347)							
D		33.49 (851)		37.44 (951)					
E MAX		38.53 (979)		43.49 (1105)			52.50 (1333)		
F		13.28 (337)							
G		18.69 (475)							
J DIA MAX		21.42 (544)		24.56 (624)					
K MAX		18.65 (474)		20.75 (527)			21.71 (551)		
L		37.34 (948)		39.45 (1002)			40.41 (1026)		
M		8.75 (222)							
N		7.20 (183)							
P		16.50 (419)							
Q		0.75 (19)							
R		14.50 (368)							
S		4							
T		5/8-11 UNC-2B							


OPERATING SPECIFICATIONS

FLANGE	PRESSURE	TEMPERATURE
ANSI Class 125	175 PSIG* (1210 KPA)	250°F (120°C)
ANSI Class 250	300 PSIG** (2070 KPA)	250°F (120°C)

Motors: All NEMA Standard (CZ or TC Frame)

* In accordance with ANSI Standard B16.1 Class 125

** In accordance with ANSI Standard B16.1 Class 250



*A & B Dimensions apply for all pump sizes.


English dimensions are in inches. Metric dimensions are in millimeters.
Metric data is presented in (). Do not use for construction purposes unless certified.

MATERIALS OF CONSTRUCTION

	BRONZE FITTED		
	STANDARD PUMP CONSTRUCTION		OPTIONAL 125# or 250#
	125# Flange	250# Flange	
Casing	Cast Iron ASTM A48/ A48M-03 Class 30A	Ductile Iron ASTM A536-84 Grade 65-45-12	N/A
Impeller	Bronze ASTM B584 ALLOY C83600 or C84400	Bronze ASTM B584 ALLOY C83600 or C84400	N/A
Wear Ring	Cast Iron	Cast Iron	Bronze ASTM B584-98A C92200
Shaft	Stainless Steel TYPE 416"Ti" or 410"Ti" ASTM A582	Stainless Steel TYPE 416"Ti" or 410"Ti" ASTM A582	N/A
Coupling	Aluminum Alloy 6061-T6	Aluminum Alloy 6061-T6	N/A
Mechanical Seal	Ceramic/EPT	Ceramic/EPT	Tungsten Carbide/EPT or Silicon- Carbide/EPT
Seal Flush Line	Copper & Brass C3600	Copper & Brass C3600	N/A

N/A = Not available

Revised: 05/31/2017



COMMENTS