

“MPT” Option E Grooved Vertical Multi-Purpose Tanks Corner Model with 2 Internal Pall Ring Baskets

SUPERSEDES: June 16, 2016

EFFECTIVE: September 3, 2019

Job:


ITEM	LOCATION	MODEL	QUANTITY	GALLONS
------	----------	-------	----------	---------

SPECIFICATIONS

- Designed and constructed per ASME Code Section VIII, Division 1.
- Construction: Carbon Steel with exterior red oxide primer finish
- Standard Design Pressure and Temperature: 125 psi @ 240°F
- Flanged inlet and outlet System Connections (standard sizes shown)
- Registered with the National Board of Pressure Vessel Manufacturers
- Integral Air Vent (Suitable for water, max. 50% glycol)
- Factory installed 2" Blow Down Valve
- Brass Flushing Cock
- 304 stainless steel coalescence pall rings
- U-1A Data Report
- (1) 2" NPT Inspection Opening – MPT0050 thru MPT0350
- (2) 4"X6" Inspection Handholes – MPT0400 thru MPT1050
- (1) 3/4" Temperature/ Pressure port on shell

OPTIONS (Consult Factory)

- Optional materials of construction
- Higher design pressures and temperatures
- Optional System Connection sizes available
- Thermal insulation
 - ☐ None
 - ☐ Chilled Water 1/2" Armaflex
 - ☐ Heating Water 1" Silicon Blanket
 - ☐ Other _____
- Optional Connection Types
 - ☐ 'T' Female NPT Threaded 2" & 2 1/2" only
Available only on sizes, MPT0050 thru MPT0350
- 3/4" NPT Temperature/Pressure Ports
 - ☐ (5) 3/4" Temperature/ Pressure ports:
One port on shell and on each nozzle
- ☐ Optional Anchor Clips
- ☐ 150 PSI Working Pressure



Size	Dia.	"C" Dim.	
		2" T	2-1/2" T
50	20	23 3/8	23 5/8
75, 100, 125	24	27 3/8	27 5/8
150, 180, 200	30	33 3/8	33 5/8
250, 300, 350	36	39 3/8	39 5/8

***Complete Model Number as shown below:**
MPT0050G04-125N1EN

SIZES & DIMENSIONS

All dimensions shown are subject to change and should not be used for pre-piping.
Contact your local Taco representative should certified dimensional drawings be required.

NOZZLE SIZES OFFERED
Circle desired size below.



MODEL NUMBER	TANK VOLUME	A DIAMETER	B	C**	D	E DIAMETER	F	G	APPROX. WEIGHT
	GAL.	INCH	INCH	INCH	INCH	INCH	INCH	SIZE	LBS.
MPT0050G_-125N1EN	50	20	43	25	11 1/2	18	12 7/8	2, 3, 4	310
MPT0075G_-125N1EN	75	24	46	29	12 5/8	20	12 7/8	2, 3, 4	360
MPT0100G_-125N1EN	100	24	61	29	12 5/8	20	12 7/8	2, 3, 4	400
MPT0125G_-125N1EN	125	24	76	29	12 5/8	20	12 7/8	2, 3, 4	450
MPT0150G_-125N1EN	150	30	60	35	14 1/4	24	13 1/2	2, 3, 4	640
MPT0180G_-125N1EN	180	30	71	35	14 1/4	24	13 1/2	2, 3, 4	720
MPT0200G_-125N1EN	200	30	78	35	14 1/4	24	13 1/2	2, 3, 4	760
MPT0250G_-125N1EN	250	36	69	41	16 3/4	30	13 1/2	3, 4, 6	890
MPT0300G_-125N1EN	300	36	82	41	16 3/4	30	13 1/2	3, 4, 6	1000
MPT0350G_-125N1EN	350	36	94	41	16 3/4	30	13 1/2	3, 4, 6	1090
MPT0400G_-125N1EN	400	48	65	53	19 5/8	44	12 7/8	4, 6, 8	1310
MPT0450G_-125N1EN	450	48	72	53	19 5/8	44	12 7/8	4, 6, 8	1380
MPT0500G_-125N1EN	500	48	79	53	19 5/8	44	12 7/8	4, 6, 8	1460
MPT0700G_-125N1EN	700	48	100	53	19 5/8	44	12 7/8	4, 6, 8	1600
MPT0850G_-125N1EN	850	54	99	59	23 1/2	50	13 1/8	4, 6, 8	2190
MPT1050G_-125N1EN	1050	60	99	65	25 3/4	54	14	6, 8, 10	2500

Nozzle Ports are shown for placement and clarity only.

** Add 1" to "C" dimension when specifying 10" nozzles

** Add 2" to "C" dimension when specifying 1.5" or thicker insulations

