



Submittal Data Information

TA Series Pumps (50 Hz – NEMA)

301-2025 I

EFFECTIVE: 08/01/24



SUPERSEDES: 04/11/14

2900 RPM MODEL 1024

JOB _____ ENGINEER _____

CONTRACTOR _____ REP. _____

ITEM NO.	MODEL NO.	IMPELLER DIA.	G.P.M.	HEAD/FT.	H.P.	ELEC. CHAR.
----------	-----------	---------------	--------	----------	------	-------------



SPECIFY ROTATION:

- ☐ Clockwise
☐ Counterclockwise

Clockwise Rotation
Viewed from the Motor End
(motor not shown)

Counterclockwise Rotation
Viewed from the Motor End
(motor not shown)

MAXIMUM ASSEMBLY WEIGHT

NEMA Motor Frame	Weight Lbs (Kg)
324TS - 326TS	1319 (598)
364TS - 365TS	1542 (699)
404TS - 405TS	1906 (865)

DIMENSIONS

Motor dimensions are approximate and vary by manufacturer and motor type.

Model No.			HP		NEMA		A DISCHARGE		B SUCTION		meter dimensions are approximate and vary by manufacturer and meter type													
Flange Size			2900 RPM		Motor Frame*		ANSI Class 125		ANSI Class 250		C	D	E	F	G	H	J	K	L	M	N	P		
1024 6 x 4 (152 x 102)			40		324TS		0.94 (24)	1.25 (32)	1.00 (25)	1.44 (37)	21.17 (538)	19.92 (506)	9.81 (249)	12.19 (310)	11.81 (300)	6.69 (170)	27.75 (705)	9.5 (241)	27.00 (686)	17.57 (446)	50.0 (1270)		30.3 (770)	
			50		326TS																			
			60		364TS																			
			75		365TS																			
			100		404TS						27.17 (690)	25.92 (658)												
					405TS																			

English dimensions are in inches. Metric dimensions are in millimeters. Metric data is presented in ().

Dimensions are subject to change without notice. Do not use for construction purposes unless certified.

* Frame size reflects TEFC enclosure. ODP enclosure is typically one size smaller. Please consult Taco or motor manufacturer for specific frame size for ODP and other non-TEFC enclosures.

MATERIALS OF CONSTRUCTION

Item	Standard	Optional
Casing	Cast Iron ASTM A48 Class 30A	N/A
Impeller	Bronze ASTM B584-836	N/A
Wear Ring	Bronze ASTM B584-836	N/A
Shaft	Carbon Steel AISI 1045	Stainless Steel AISI 420
Insert	Cast Iron ASTM A48 Class 30A	N/A
Shaft Sleeve	Bronze ASTM B584-836	Stainless Steel AISI 420

N/A - Not Available

OPERATING SPECIFICATIONS

	Standard	Optional
Flange	ANSI Class 125	ANSI Class 250
Pressure	175 PSIG* (1210 KPA)	300 PSIG** (2070 KPA)
Temperature	250°F (120°C)	250°F (120°C)


Motors: All NEMA Standard (T Frame)
* In accordance with ANSI Standard B16.1 Class 125
** In accordance with ANSI Standard B16.1 Class 250 Dim.

FEATURES

	Standard	Optional
Wear Rings	Case Wear Rings	N/A
Seal Flushing	Recirculation Line	Filter & Abrasive Separators
Motors	All Standard NEMA Motors	
Base	Drip Type Base	
Additional Options	Packed Stuffing Box Two Rotation Options Balanced Mechanical Seals	



Model 1024	2900 RPM	Curve no. 1388
TA Series	August 1, 2024	Min. Imp. Dia. 7.50" Size 4 X 6 X 9.50



Comments: