



Submittal Data Information

TA Series Pumps

301-620

EFFECTIVE: 08/01/24

SUPERSEDES: 01/17/14



1160 RPM MODEL 1548

JOB _____ ENGINEER _____


CONTRACTOR _____ REP. _____

ITEM NO.	MODEL NO.	IMPELLER DIA.	G.P.M.	HEAD/FT.	H.P.	ELEC. CHAR.
----------	-----------	---------------	--------	----------	------	-------------

WEIGHT _____ PUMP/MOTOR _____



Clockwise Rotation
Viewed from the Motor End
(motor not shown)



Counterclockwise Rotation
Viewed from the Motor End
(motor not shown)

SPECIFY ROTATION:

- ☐ Clockwise
☐ Counterclockwise

MAXIMUM ASSEMBLY WEIGHT

Motor Frame	Weight Lbs (Kg)
324T - 326T	2229 (1011)
364T - 365T	2481 (1125)
404T - 405T	2793 (1267)
444T - 445T	3416 (1549)

DIMENSIONS

Motor dimensions are approximate and vary by manufacturer and motor type.

			A DISCHARGE				B SUCTION		C	D	E	F	G	H	J	K	L	M	N	P
Model No. Flange Size	HP 1160 RPM	Motor Frame	ANSI Class 125	ANSI Class 250	ANSI Class 125	ANSI Class 250														
1548 8 x 6 (203 x 152)	25	324T	1.00 (25)	1.44 (37)	1.13 (29)	1.62 (41)	27.17 (690)	25.92 (658)	17.69 (449)	20.06 (510)	14.50 (368)	10.62 (270)	34.13 (867)	13.52 (343)	43.25 (1099)	25.44 (646)	64.0 (1626)	30.3 (770)		
	30	326T																33.4 (848)		
	40	364T																38.3 (973)		
	50	365T																80.0 (2032)	44.6 (1133)	
	60	404T																		
	75	405T																		
	100	444T																		

English dimensions are in inches. Metric dimensions are in millimeters. Metric data is presented in ().
Dimensions are subject to change without notice. Do not use for construction purposes unless certified.

MATERIALS OF CONSTRUCTION

Item	Standard	Optional
Casing	Cast Iron ASTM A48 Class 30A	N/A
Impeller	Bronze ASTM B584-836	N/A
Wear Ring	Bronze ASTM B584-836	N/A
Shaft	Carbon Steel AISI 1045	Stainless Steel AISI 420
Insert	Cast Iron ASTM A48 Class 30A	N/A
Shaft Sleeve	Bronze ASTM B584-836	Stainless Steel AISI 420

N/A - Not Available

OPERATING SPECIFICATIONS

	Standard	Optional
Flange	ANSI Class 125	ANSI Class 250
Pressure	175 PSIG* (1210 KPA)	300 PSIG** (2070 KPA)
Temperature	250°F (120°C)	250°F (120°C)

Motors: All NEMA Standard (T Frame)

* In accordance with ANSI Standard B16.1 Class 125

** In accordance with ANSI Standard B16.1 Class 250 Dim.

FEATURES

	Standard	Optional
Wear Rings	Case Wear Rings	N/A
Seal Flushing	Recirculation Line	Filter & Abrasive Separators
Motors	All Standard NEMA Motors	
Base	Drip Type Base	
Additional Options	Packed Stuffing Box Two Rotation Options Balanced Mechanical Seals	



Model 1548


1160 RPM

Curve no. 819
Min. Imp. Dia. 14.17"

TA Series

August 1, 2024

Size 6 X 8 X 18.75



Comments: _____