

Submittal Data Information

TA Series Pumps (50 Hz – IEC)

301-2057 I

EFFECTIVE: January 17, 2014

SUPERSEDES: September 1, 2010



1450 RPM MODEL 2530

JOB _____ ENGINEER _____


CONTRACTOR _____ REP. _____

ITEM NO.	MODEL NO.	IMPELLER DIA.	G.P.M.	HEAD/FT.	H.P.	ELEC. CHAR.
----------	-----------	---------------	--------	----------	------	-------------

WEIGHT _____ PUMP/MOTOR _____



Clockwise Rotation
Viewed from the Motor End
(motor not shown)



Counterclockwise Rotation
Viewed from the Motor End
(motor not shown)

SPECIFY ROTATION:

- ☐ Clockwise
☐ Counterclockwise

MAXIMUM ASSEMBLY WEIGHT

IEC Motor Frame	Weight Lbs (Kg)
180L	1749 (793)
200L	1861 (844)
225S	1983 (899)
225M	2060 (934)
250M	2190 (993)
280S	2474 (1122)

DIMENSIONS

Motor dimensions are approximate and vary by manufacturer and motor type.

Model No. Flange Size	KW 1450 RPM	IEC Motor Frame	A DISCHARGE		B SUCTION		C	D	E	F	G	H	J	K	L	M	N	P
			ANSI Class 125	ANSI Class 250	ANSI Class 125	ANSI Class 250												
2530 10 x 10 (254 x 254)	22	180L	1.19 (30)	1.88 (48)	1.19 (30)	1.88 (48)	27.17 (690)	25.91 (658)	15.75 (400)	16.94 (430)	13.63 (346)	9.81 (249)	31.32 (796)	11.57 (294)	38.06 (967)	25.44 (646)	57.0 (1448)	28.7 (729)
	30	200L																29.9 (759)
	37	225S																31.7 (805)
	45	225M																32.7 (831)
	55	250M															60.0 (1524)	35.8 (909)
	75	280S																38.7 (983)

English dimensions are in inches. Metric dimensions are in millimeters. Metric data is presented in ().
Dimensions are subject to change without notice. Do not use for construction purposes unless certified.

MATERIALS OF CONSTRUCTION

Item	Standard	Optional
Casing	Cast Iron ASTM A48 Class 30A	N/A
Impeller	Bronze ASTM B584-836	N/A
Wear Ring	Bronze ASTM B584-836	N/A
Shaft	Carbon Steel AISI 1045	Stainless Steel AISI 420
Insert	Cast Iron ASTM A48 Class 30A	N/A
Shaft Sleeve	Bronze ASTM B584-836	Stainless Steel AISI 420

N/A - Not Available

OPERATING SPECIFICATIONS

	Standard	Optional
Flange	ANSI Class 125	ANSI Class 250
Pressure	175 PSIG* (1210 KPA)	300 PSIG** (2070 KPA)
Temperature	250°F (120°C)	250°F (120°C)

Motors: All NEMA Standard (T Frame)

* In accordance with ANSI Standard B16.1 Class 125

** In accordance with ANSI Standard B16.1 Class 250 Dim.

FEATURES

	Standard	Optional
Wear Rings	Case Wear Rings	N/A
Seal Flushing	Recirculation Line	Filter & Abrasive Separators
Motors	All Standard NEMA Motors	
Base	Drip Type Base	
Additional Options	Packed Stuffing Box Two Rotation Options Balanced Mechanical Seals	



Model 2530


1450 RPM

Curve no. 1899

TA Series

August 1, 2024

Min. Imp. Dia. 9.65"
Size 10 X 10 X 12.50



Comments: _____